

1.6T Container Trailer ACD 1600-2



General Specification

Length	3451mm	Wheel Base	1580mm
Width	1790mm	Tyres	4.00-8 solid rubber
Height (ULD locks up)	562mm	Towing speed max	24 km/h
Loading height	508mm	Turning radius	Turntable steering, 55°
Empty weight	760kg	ULD carry	LD1,LD2,LD3
Capacity	1600kg	Rollers	Quick disconnect, 76mm diameter

✓ Main Features

- ✓ Conforms to IATA, Australia and New Zealand standard specifications
- ✓ Low total cost ownership
- ✓ Turntable steering
- ✓ Part brake actuated by tow bar in upright or down position. Foot-pedal release.
- ✓ Finishing by peening and then primed with 2 top coats, or by hot dip galvanising
- ✓ Rollers are quick release type with spring lock engagement one end.
- ✓ Front rollers are impact type with 4 mm wall thickness.
- ✓ Elastic cushion rubber tyres 400x8 for quiet and low-vibration operation
- ✓ Tow bar mounted cushion bumper that protects tarmac surface
- ✓ 6 Platform support idle bearing
- ✓ Option for safety panel infill and painted with "No Step" between rollers.
- ✓ Adjustable ULD locks - Newly designed to reduce ULD base width between locks, accommodating in-service wear and extending the life of the dolly.

✓ Safety Features

- ✓ Red warning paint was applied to the Tow bar, hitch, locks and remote handles.
- ✓ Safety yellow applied to corners, pedals, and along the centre walkway
- ✓ LOCK & UNLOCK marking on trailer
- ✓ Lock handles have unrestricted hand access; handle grips are profiled.
- ✓ Over design, lock mechanism capable of restraining one fully loaded dolly on a 2-degree slop